

MORNSUN®

15-600W

Enclosed Switching Power Supply

► *LM/LMF/LI/LIF Series*



Low cost



Robust



Fast

Made in India



* For detailed information, please refer to the datasheet.

MORNSUN®

E-mail: info@mornsun.cn

Website: www.mornsun-power.com

Facebook/Linkedin: Mornsun Power



Distributor: Myzek Technologies

Contact: Mit Pandya

E-mail: info@myzektechnologies.com

Tel: 91-8347469999

Address: 318, Matrix Plaza, Jashoda Hathijan Road,

Vinzol, Vatva, G.I.D.C., Ahmedabad, Gujarat, India 382440

» Reliable Performance «

- Isolation voltage up to 4000VAC
- Output short circuit, over-current, over-voltage protection
- -30°C to +70°C operating temperature
- EMI: CISPR32/EN55032 CLASS B
- Complete certifications: CE/UL/CB/CCC

Made in India



Quick response
with local service



Customization
is available



FAE/R&D
technical support

» Wide Selection «

Series	Power (W)	Input voltage (VAC)	NO. of outputs	Package
LMFxx-20B ¹ (with PFC)	75-320	85-264	1	Enclosed
LMxx-23B ¹	15-150	85-305	1	Enclosed
LMxx-20B ¹	35-150	85-264	1	Enclosed
LMxx-10B ¹	200-350	90-132/180-264 (by switch)	1	Enclosed
LMxx-22B ¹	35-150	165-264	1	Enclosed
LMxx-12B ¹	200-350	176-264	1	Enclosed
LMxx-12B ^{1, 2} (Coming Soon)	450-600	176-264	1	Enclosed
LMxx-10A/C/D ²	35-100	85(90)-264	2/3	Enclosed
Llxx-20BxxPR2	30-100	85-264	1	Din-Rail
Llxx-20BxxR2/R2S	75-120	90-264	1	Din-Rail
LlFxx-10BxxR2 (Coming Soon)	120-480	85-264	1	Din-Rail

Notes: 1.Conformal coating (series with suffix “-Q”) is acceptable, terminal cover (series with suffix “-C”) is optional.
2.Conformal coating (series with suffix “-Q”) is acceptable.

* For detailed information, please refer to the datasheet.

MORNSUN®

E-mail: info@mornsun.cn

Website: www.mornsun-power.com

Facebook/Linkedin: Mornsun Power



Distributor: Myzek Technologies

Contact: Mit Pandya

E-mail: info@myzektechnologies.com

Tel: 91-8347469999